



PMB072T060SS-255A

5A/60V⁽¹⁾, low VF Planar MOS barrier diode

Mechanical Data

Chip Drawing	Item	Information	
	Die Size (A)	1828μm	72.0 mil
	Top Metal Pad Size (B)	1728μm	68.0mil
	Chip Size (C)	/	/
	Wafer Thickness (D)	255 μm	10.0 mil
	Scribe Line Width (E)	80 μm	3.15 mil
	Wafer Size	6 inch	
	Top Side Metallization	PMB072T060SS-255A	Ag
	Back Side Metallization	Ti Ni Ag	
	Recommended Storage Environment	Stored in original container, in dry nitrogen, (6 months at an ambient temperature of 23℃±3℃)	

Electrical Characteristics (T_J=25)⁽²⁾

Parameter	Description	Min.	Typ.	Max.	Unit	Test Condition
V _{BR}	Reverse Breakdown Voltage	62	67	-	V	I _R =300μA
V _F	Instantaneous Forward Voltage	-	0.46	0.50	V	I _F =5A ⁽³⁾
I _R	Reverse Leakage Current	-	50	120		V _R =60V
T _J , T _{STG}	Operating and Storage Temperature	-40℃ to 150℃ Max				

Note:

(1) The preliminary wafer datasheet only for reference;

(2) This characteristics assumes the dies are assembled in SMB packages. Actual performance may degrade when assembled. YJ