


1-Line, Uni-directional, Transient Voltage Suppressor



DFN0603-2L

Features

- ✕ Stand-off voltage: 2.1V Max
- ✕ Transient protection for each line according to
 - IEC61000-4-2(ESD): 030kV (contact)
 - IEC61000-4-4 (EFT): 40A (5/50ns)
 - IEC61000-4-5(surge): 22A (8/20>s)
- ✕ Low leakage current
- ✕ Low clamping voltage
- ✕ Low clamping voltage:
 $V_{CL} = 4.5V$ typ. @ $I_{PP} = 16A$ (TLP)
- ✕ RoHS Compliant

Applications


- ✕ Power supply protection
- ✕ Power management

Mechanical Data

- ✕ Package: DFN0603-2L
- ✕ Lead Finish: Matte Tin
- ✕ Case Material: 0Green0 Molding Compound
- ✕ Moisture Sensitivity: Level 3 per J-STD-020
- ✕ Marking Information: See Below

Pin1 **J2** Pin2

Definitions of electrical characteristics





ESD2V1LZA

Maximum Ratings

PARAMETER	SYMBOL	LIMITS	UNIT
Peak pulse power ($t_p = 8/20\mu s$)	P_{pk}	180	W
Peak pulse current ($t_p = 8/20\mu s$)	I_{PP}	22	A
ESD according to IEC61000-4-2 air discharge	V_{ESD}	±30	kV
ESD according to IEC61000-4-2 contact discharge		±30	
Junction temperature	T_J	125	°C
Operating temperature	T_{OP}	-40~85	°C
Storage temperature	T_{STG}	-55~150	°C

Electrical Characteristics

2.5


Unless otherwise specified

PARAMETER	Symbol	UNIT	Conditions	Min	Typ	Max
Reverse maximum working voltage	V_{RWM}	V				2.1



Ω Characteristics (Typical)

Fig.1 8/20 μ s waveform per IEC61000-4-5





Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.21yangjie.com](http://www.21yangjie.com) , or consult your nearest Yangjie's sales office for further assistance.