■ NMOS Electrical Characteristics (T_J=25 unless otherwise noted)

Parameter	Symbol	Conditions	Min	Typ	Max	Units
Static Parameter						
Drain-Source Breakdown Voltage	BV_{DSS}	V_{GS}= 0V, I_D=250μA	60	-	-	V
Zero Gate Voltage Drain Current	I_{DSS}	V_{DS}=60V, V_{GS}=0V	-	-	1	μA
		V_{DS}=60V, V_{GS}=0V, Tj=150	-	-	100	
Gate-Body Leakage Current	I_{GSS}	V_{GS}= 20V, V_{DS}=0V	-	-	100	nA
Gate Threshold Voltage	$V_{GS(th)}$	V_{DS}= V_{GS}, I_D=250μA	1	1.5	2.0	V
Static Drain-Source On-Resistance	$R_{DS(on)}$	V_{GS}=10V, I_D=20A	-	23	30	mΩ
		V_{GS}				

■ NMOS Typical Electrical and Thermal Characteristics Diagrams



Figure 1. Output Characteristics



Figure 2. Transfer Characteristics



Figure 3. Capacitance Characteristics



Figure 4. Gate Charge



Figure 5. On-Resistance vs Gate to Source Voltage



Figure 6. Normalized On-Resistan



Figure 7. $R_{DS(on)}$ VS Drain Current



Figure 8. Forward characteristics of reverse diode



Figure 9. Normalized breakdown voltage



Figure 10. Normalized Threshold voltage



Figure 11. ~~Current~~ dissipation







Figure 5. On-Resistance vs Gate to Source Voltage Fi



Figure 11. Current dissipation



Figure 12. Power dissipation



Figure 13. Maximum Transient Thermal Impedance



Figure 14. Safe Operation Area

■ **PDFN5060-8L-E-1.1MM**

Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design.