





Electrical Characteristics ($T_J=25$ unless otherwise noted)

Parameter	Symbol
-----------	--------



Typical Performance Characteristics




Figure7. Normalized Gate Threshold Voltage




Figure8.Safe Operation Area





Figure9.Normalized Maximum Transient thermal impedance



PDFN5060-8L-B-1.1MM Package information



Top View

Bottom View

Side View

SYMBOL	MILLIMETER		
	MIN	NOM	MAX
D	5.15	5.35	5.55
E	5.95	6.15	6.35
A	1.00	1.10	1.20
A1			

Note:

- 1.Controlling dimension:in millimeters.
- 2.General tolerance:±0.10mm.
- 3.The pad layout is for reference purposes only.



Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.21yangjie.com](http://www.21yangjie.com)