




- Epoxy meets UL-94 V-0 flammability rating
- Halogen free available upon request by adding suffix "HF"
- Moisture Sensitivity Level 1
- Marking: J6

(Ta=25 unless otherwise noted)

Collector-Base Voltage	V_{CBO}	V		50
Collector-Emitter Voltage	V_{CEO}	V		45
Emitter-Base Voltage	V_{EBO}	V		5
Collector Current	I_C	A		0.1
Collector Power Dissipation	P_C	W		0.2
Operation Junction Temperature	T_j			150
Storage Temperature	T_{stg}			-55 to +150 °C

	Symbol	Unit	Conditions	Min	Typ	Max
Collector-base breakdown voltage	V_{CBO}	V	$I_C=100\mu A, I_E=0$	50		
Collector-emitter breakdown voltage	V_{CEO^*}					

	I_{CEO}	μA	$V_{CE}=35V, I_B=0$			0.1
Emitter-Base cut-off current	I_{EBO}	μA	$V_{EB}=3V, I_C=0$			0.1
DC current gain	h_{FE}	V	$V_{CE}=5V, I_C=1mA$	200		1000
Collector-emitter saturation voltage	$V_{CE(sat)}$	V	$I_C=100mA, I_B=5mA$			0.3
Base-emitter saturation voltage	$V_{BE(sat)}$	V	$I_C=100mA, I_B=5mA$			1





■

■

(Example)

S9014	F2	Approximate 0.008	3000	30000	120000	7" reel





The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & r