



Surface Mount Super Fast Recovery Rectifier



Features

- Low profile package
- Ideal for automated placement
- Glass passivated chip junction
- High forward surge capability
- Super Fast reverse recovery time

For use in high frequency rectification of power supplies, inverters, converters, and freewheeling diodes for consumer and telecommunication.



Mechanical Data

Package: SMBF

Molding compound meets UL 94 V-0 flammability rating, RoHS-compliant, halogen-free

Terminals: Tin plated leads, solderable per J-STD-002 and JESD22-B102

Polarity: Cathode line denotes the cathode end

Maximum Ratings ($T_a=25$ Unless otherwise specified)

| PARAMETER | SYMBOL | UNIT | ES2ABF | ES2BBF | ES2CBF | ES2DBF | ES2FBF | ES2GBF | ES2HBF | ES2JBF | ES2KBF |
|--|-----------|--------|------------|--------|--------|--------|--------|--------|--------|--------|--------|
| Device marking code | | | ES2ABF | ES2BBF | ES2CBF | ES2DBF | ES2FBF | ES2GBF | ES2HBF | ES2JBF | ES2KBF |
| Maximum Repetitive Peak Reverse Voltage | V_{RRM} | V | 50 | 100 | 150 | 200 | 300 | 400 | 500 | 600 | 800 |
| Maximum RMS Voltage | V_{RMS} | V | 35 | 70 | 105 | 140 | 210 | 280 | 350 | 420 | 560 |
| Maximum DC blocking Voltage | V_{DC} | V | 50 | 100 | 150 | 200 | 300 | 400 | 500 | 600 | 800 |
| Average rectified output current @60Hz sine wave, resistance load, TL (Fig.1) | I_o | A | 2.0 | | | | | | | | |
| Forward Surge Current (Non-repetitive) @60Hz Half-sine wave, 1 cycle, $T_j=25$ | I_{FSM} | A | 50 | | | | | | | | |
| Forward Surge Current (Non-repetitive) @1ms, square wave, 1 cycle, $T_j=25$ | | | 100 | | | | | | | | |
| Current squared time @1ms t 8.3ms $T_j=25$ Rating of per diode | I^2t | A^2s | 10.375 | | | | | | | | |
| Typical junction capacitance @Measured at 1MHz and Applied Reverse Voltage of 4.0 V.D.C | C_j | pF | 31 | | | 17 | | | 12 | | 12 |
| Storage temperature | T_{stg} | | -55 ~ +150 | | | | | | | | |
| Junction temperature | T_j | | -55 ~ +150 | | | | | | | | |

Electrical Characteristics $T_a=25$ Unless otherwise specified

| | R | SYMBOL | | | | ES2CBF | ES2DBF | ES2FBF | ES2GBF | ES2HBF | ES2JBF | ES2KBF |
|---|----------|---------|------------------------------------|---|-------------|--------|--------|--------|--------|--------|--------|--------|
| | | | | | | F | F | F | F | F | F | BF |
| Maximum instantaneous forward voltage drop per diode | V_F | V | $I_{FM}=21$ | M | $I_{FM}=21$ | b | | | b | | | |
| | t_{tr} | ns | $I_F=0.5A, I_R=1.0A, I_{rr}=0.25A$ | | | 35 | | | | | | |
| Maximum DC reverse current at rated DC blocking voltage per diode | I_R | μA | $T_j=25$ | | | 5.0 | | | | | | |
| | | | $T_j=125$ | | | 100 | | | | | | |



ES2ABF THRU ES2KBF

Thermal Characteristics $T_a=25$ Unless otherwise specified

| PARAMETER | SYMBOL | UNIT | ES2ABF | ES2BBF | ES2CBF | ES2DBF | ES2FBF | ES2GBF | ES2HBF | ES2JBF | ES2KBF |
|----------------------------|----------------|------|--------|--------|--------|--------|--------|--------|--------|--------|--------|
| Typical Thermal Resistance | $R_{JA}^{(1)}$ | /W | 60 | | | | | | | | |
| | $R_{JL}^{(1)}$ | | 20 | | | | | | | | |
| | $R_{JC}^{(1)}$ | | 15 | | | | | | | | |

Note:
 (1) Thermal resistance from junction to ambient and from junction to lead mounted on P.C.B. with 0.3" x 0.3" (8.0 mm x 8.0 mm) copper pad areas

Characteristics (Typical)

FIG1 I_o TL Curve




FIG2 Surge Forward Current Capability






FIG4: Typical Reverse Characteristics





ES2ABF THRU ES2KBF

Suggested pad layout



| Dim | Milimeters |
|-----|------------|
| P1 | 6.20 |
| P2 | 2.40 |
| Q1 | 1.90 |
| Q2 | 2.20 |

