




Fast Recovery Rectifier



Features

- High efficiency
- High current capability
- High reliability
- High surge current capability
- Low power loss
- Glass passivated chip junction
- Solder dip 275 °C max. 7 s, per JESD 22-B106

Mechanical Data

- **Package:** R-1

Molding compound meets UL 94 V-0 flammability rating,
RoHS-compliant, Halogen free

- **Terminals:** Tin plated leads, solderable per J-STD-002 and JESD22-B.106

				1F2G	1F3G	1F4G	1F5G	1F6G	1F7G
Device marking code			1F1G	1F2G	1F3G	1F4G	1F5G	1F6G	1F7G
Maximum Repetitive Peak Reverse Voltage	VRRM	V	50	100	200	400	600	800	1000
Maximum RMS Voltage	VRMS	V	35	70	140	280	420	560	700
Maximum DC blocking Voltage	VDC	V	50	100	200	400	600	800	1000
Average Forward Current Continuous load, Ta=70	IF(AV)	A	1.0						
Non-repetitive Forward Surge Current Single pulse, Tj=25	IFSM	A	30						
Non-repetitive Forward Surge Current Single pulse, Tj=25			60						
Forward Bias Squared time @1ms≤t≤8.3ms Tj=25	I²t	A²s	3.375						
Typical junction capacitance @Measured at 1MHz and Applied Reverse Voltage of 4.0 V.DC	Cj	pF	10					8	
Storage Temperature	Tstg		-55 ~ +150						
Junction Temperature	Tj		-55 ~ +150						

■Electrical Characteristics Ta=25 Unless otherwise specified

PARAMETER	SYMBOL	UNIT	1F2G	1F3G	1F4G	1F5G	1F6G	1F7G
-----------	--------	------	------	------	------	------	------	------

	tr	ns	IF = 0.5A, IR = 1.0A , Itr = 0.25A	150	250	500
--	----	----	---------------------------------------	-----	-----	-----




1F1G THRU 1F7G

■Thermal Characteristics $T_a=25$ Unless otherwise specified

PARAMETER	SYMBOL	UNIT	1F1G	1F2G	1F3G	1F4G	1F5G	1F6G	1F7G
-----------	--------	------	------	------	------	------	------	------	------



■ Outline Dimensions



R-1		
Dim	Min	Max
A	3.00	3.30
B	2.00	2.70
C	25.4	/
D	0.53	0.64



Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.21yangjie.com](http://www.21yangjie.com) , or consult your nearest Yangjie's sales office for further assistance.