





General Purpose Rectifier



Features

- High efficiency
- High current capability
- High reliability
- High surge current capability
- Low power loss
- Glass passivated chip junction
- Solder dip 275 °C max. 7 s, per JESD 22-B106

Typical Applications

For use in general purpose rectification of power supplies, inverters, converters, and freewheeling diodes for consumer, and telecommunication.

Mechanical Data

- **Package:** DO-204AC(DO-15)
Molding compound meets UL 94 V-0 flammability rating, RoHS-compliant
- **Terminals:** Tin plated leads, solderable per J-STD-002 and JESD22-B102
- **Polarity:** Color band denotes cathode end

Maximum Ratings (Ta=25 °C Unless otherwise specified)

PARAMETER Peak Reverse Voltage V

	RRM	V	50	100	200	400	600	800	1000
Maximum RMS Voltage	V _{RMS}	V	35	70	140	280	420	560	700
Maximum DC blocking Voltage	V _{DC}	V	50	100	200	400	600	800	1000
Average Forward Current @60Hz sine wave, Resistance load, Ta = 25 °C	I _{F(AV)}	A	2.5						
Forward Surge Current (Non-repetitive) @60Hz Half-sine wave, 1 cycle, Tj=25 °C	I _{FSM}	A	120						
Forward Surge Current (Non-repetitive) @1ms, square wave, 1 cycle, Tj=25 °C			240						
Current Squared time	W	V							
7\SLFDO MXQFWLRQ FDSDFLWDQFH #0HDVXUHG DW 0+J DQG \$\$\$OLN 5HYHUVH 9ROWDJH RI 9 ' &									
6WRUDJH 7HPSHUDWXUH	7VWJ		-55 ~ +150						
Junction Temperature	T _j		-55 ~ +150						

Electrical Characteristics Ta=25 °C Unless otherwise specified


PARAMETER	SYMBOL	UNIT	TEST CONDITIONS	RL251G	RL252G	RL253G	RL254G	RL255G	RL256G	RL257G
Maximum instantaneous forward voltage drop per diode	V _F	V	I _{FM} =2.5A	1.1						
Maximum DC reverse current at rated DC blocking voltage per diode	I _R	μA	T _j =25	2.5						
			T _j =125	50						

v7KHUPDO &KDUDÄFWHU&QVLFVVRWKHUAŁLVH VSHFLILHG

3\$5\$0(7(5	6<0%2/	81,7	5/ *	5/ *	5/ *	5/ *	5/ *	5/ *	5/ *
-------------	--------	------	------	------	------	------	------	------	------



■ Outline Dimensions



DO-204AC(DO-15)		
Dim	Min	Max
A	5.80	7.60
B	2.60	3.60
C	25.4	/
D	0.70	0.90



Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.21yangjie.com](http://www.21yangjie.com) , or consult your nearest Yangjie's sales office for further assistance.