


- Guardring for overvoltage protection
- Low power loss
- Extremely fast switching
- High forward surge capability
- High frequency operation
- Solder dip 260 °C max. 10 s, per JESD 22-B106

Color band denotes the cathode end

■ (Ta=25 Unless otherwise specified)

Device marking code			SS82	SS84	SS86	SS810	SS815	SS820
Repetitive Peak Reverse Voltage	V_{RRM}	V	20	40	60	100	150	200
Average Rectified Output Current @60Hz sine wave, Resistance load, Ta (FIG.1)	I_O	A	8.0					
Surge(Non-repetitive)Forward Current @60Hz Half-sine wave,1 cycle, Ta=25	I_{FSM}	A	120					
Storage Temperature	T_{stg}		-55 ~+150					
Junction Temperature	T_j		-55~+125		-55 ~+150			

■ (Ta=25 Unless otherwise specified)

				0.2		0.1		
			Ta=100	20		5.0		
Typical junction capacitance	Cj	pF	Measured at 1MHz and Applied Reverse Voltage of 4.0 V.D.C.	450	350	270	180	


Note1:Pulse test:300uS pulse width,1% duty cycle

Note2:Pulse test:pulse width 40mS



■

DO-214AB (SMC)		
Dim	Min	Max
A	6.60	7.11
B	2.85	3.27
C	5.59	6.22
D	7.75	8.13
E	1.99	2.61
F	0.15	0.31
G	0.76	1.52
H	0.05	0.20



DO-214AB (SMC)		
Dim	Min	Max
P1		



The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility for the consequences of such use.

This document is the property of Yangzhou Yangjie Electronic Technology Co., Ltd. and is not to be distributed outside the company without prior written permission.