


- UL recognition, file #E230084
- Glass passivated chip junction
- Ideal for printed circuit boards
- High surge current capability
- Solder dip 275 °C max. 7 s, per JESD 22-B106

General purpose use in AC/DC bridge full wave rectification for monitor, TV, printer, power supply, switching mode power supply, adapter, audio equipment, and home appliances applications.

- : GBU
- Molding compound meets UL 94 V-0 flammability rating, RoHS-compliant
- : Tin plated leads, solderable per J-STD-002 and JESD22-B102
- As marked on body

■ (Ta=25 Unless otherwise specified Å Tc=100- IO A

	Without heatsink Ta=25 -			
				3.2
Forward Surge Current (Non-repetitive) @60Hz Half-sine wave,1 cycle, Tj=25 -	IFSM	A		175
Current squared time @1ms≤t≤8.3ms Tj=25 - , Rating of per diode	I²t	A²S		127
Storage temperature	Tstg	-		-55 ~ +150
Junction temperature	Tj	-		-55 ~ +150
Dielectric strength @ Terminals to case, AC 1 minute	Vdis	KV		2.5
Mounting torque @Recommend torque Ö5kg cm	Tor	kg cm		8

■ ÅTa=25 Unless otherwise specified Å

Maximum reverse recovery time	T _{RR}	ns	I _F =0.5A, I _R =1.0A, I _{RR} =0.25A	35
Maximum instantaneous forward voltage drop per diode	V _F	V	I _{FM} =5.0A	1.7
Maximum DC reverse current at rated DC blocking voltage per diode	I _R	µA	T _j =25 -	5
			T _j =125 -	100
Typical junction capacitance	C _j	pF	Measured at 1MHz and Applied Reverse Voltage of 4.0 V.D.C	54



■ $T_a=25$ Unless otherwise specified $^{\circ}C$


Thermal Resistance	Between junction and ambient, Without heatsink	R θ J-A	- /W	20
	Between junction and case, With heatsink	R θ J-C		2

Note: Device mounted on 75mm x 45mm x 5.5mm Aluminum Plate Heatsink.

■ (Example)

	B1	Approximate 3.96	20	1000	2000	TUBE

Characteristics



■

Dim	Min	Max
A	21.80	22.30
B	18.30	18.80
C	17.50	18.00
D	3.30	3.90
E	7.10	7.50
F	5.50	5.90
G	1.91	2.54
H	2.06	2.54
I	1.02	1.27
J	4.83	5.33
K	3.30	3.56
L	2.40	2.66
M	0.46	0.56



The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.21yangjie.com](http://www.21yangjie.com) , or consult your nearest Yangjie's sales office for further assistance.