




Bridge Rectifiers

Tin plated leads, solderable per
J-STD-002 and JESD22-B102



- **Polarity:** As marked on body

■ Maximum Ratings ($T_a=25^\circ\text{C}$ Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	MBLSK22S	MBLSK24S	MBLSK26S	MBLSK28S	MBLSK210S	MBLSK215S	MBLSK220S
Device marking code			MBLSK22S	MBLSK24S	MBLSK26S	MBLSK28S	MBLSK210S	MBLSK215S	MBLSK220S
Repetitive peak reverse voltage	VRRM	V	20	40	60	80	100	150	200
Average rectified output current @60Hz Half-sine wave, Resistance load, TL (FIG.1)	I _O	A	2.0						
Surge(non-repetitive)forward current @ 60Hz half-sine wave,1 cycle, T _j =25	I _{FSM}	A	50						
Current squared time @1ms≤t≤8.3ms T _j =25									

	S Y M B O L	U N I T	T E S T C O N D I T I O N	M B L S K 2 2 S	M B L S K 2 4 S	M B L S K 2 6 S	M B L S K 2 8 S	M B L S K 2 1 0 S	M B L S K 2 1 5 S	M B L S K 2 2 0 S
Maximum instantaneous forward voltage drop per diode	V _F	V	I _{FM} =1.0A	0.50		0.70	0.85		0.90	
Maximum DC reverse current at rated DC blocking voltage per diode@ V _{RM} =V _{RRM}	I _{RRM}	uA	T _a =25	500			100			
			T _a =100	10000			5000			



MBLSK22S THRU MBLSK220S


■ Thermal Characteristics $T_a=25$ Unless otherwise specified

PARAMETER		SYMBOL	UNIT	MBLSK22S	MBLSK24S	MBLSK26S	MBLSK28S	MBLSK210S	MBLSK215S	MBLSK220S
Thermal Resistance	Between junction and ambient, On alumina substrate	R θ J-A	/W	76.0						
	Between junction and ambient, On glass-epoxi substrate	R θ J-A		134.0						
	Between junction and lead	R θ J-L		20.0						

■ Ordering Information (Example)

PREFERED P/N	PACKING CODE	UNIT WEIGHT(g)	MINIIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
MBLSK22S-MBLSK220S	F1	Approximate 0.083	4000	8000	64000	13' reel
MBLSK22S-MBLSK220S	F3	Approximate 0.083	5000	10000	80000	13' reel

■ Characteristics(Typical)





MBLSK22S THRU MBLSK220S

Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.21yangjie.com](http://www.21yangjie.com) , or consult your nearest Yangjie's sales office for further assistance.